








| BS-2004 COPPER WIRES |                 |              |  | Telephone Cables |            |              |
|----------------------|-----------------|--------------|---|------------------|------------|--------------|
| Size                 | 250/440V CU/PVC |              |   | Sizes            | Registered | Unregistered |
|                      | Registered      | Unregistered |   | 1 Pair           | 2,457      | 2,520        |
|                      | S/C             | S/C          |   | 2 Pair           | 5,120      | 5,251        |
| 3/.029               | 4,364           | 4,476        | 3 Pair  | 7,195            | 7,379      |              |
| 7/.029               | 9,141           | 9,376        | 4 Pair  | 8,649            | 8,871      |              |
|                      |                 |              | 5 Pair  | 11,290           | 11,579     |              |

|    | Size   | Coaxial Cable |              |    |
|--|--------|---------------|--------------|---|
|  |        | Registered    | Unregistered |   |
|  | RG - 6 | 10,803        | 11,080       |   |
|  | RG - 7 | 11,900        | 12,205       |   |

**WIRING CABLES PRICE LIST**

**SPECIFICATION: BS 6004, IEC 60228 (450/750V,300/500V)**

| Size                      | 450/750V CU/PVC |              | 300/500V CU/PVC/PVC |              | 300/500V CU/PVC/PVC |              | 300/500V CU/PVC/PVC |              |
|---------------------------|-----------------|--------------|---------------------|--------------|---------------------|--------------|---------------------|--------------|
|                           | Registered      | Unregistered | Registered          | Unregistered | Registered          | Unregistered | Registered          | Unregistered |
|                           | S/C             | S/C          | 2 - CORE            | 2 - CORE     | 3 - CORE            | 3 - CORE     | 4 - CORE            | 4 - CORE     |
| 1 mm <sup>2</sup>         | 3,256           | 3,339        | 7,988               | 8,192        | 13,835              | 14,189       | 16,745              | 17,175       |
| 1.5 mm <sup>2</sup> Solid | 4,877           | 5,002        | 14,021              | 14,380       | 19,717              | 20,223       | 24,995              | 25,636       |
| 1.5 mm <sup>2</sup> Std.  | 5,174           | 5,306        | 14,862              | 15,243       | 20,751              | 21,284       | 26,158              | 26,829       |
| 2.5 mm <sup>2</sup> Solid | 7,847           | 8,048        | 19,937              | 20,449       | 28,482              | 29,213       | 36,271              | 37,201       |
| 2.5 mm <sup>2</sup> Std.  | 8,574           | 8,793        | 20,750              | 21,282       | 29,761              | 30,524       | 38,131              | 39,109       |
| 4 mm <sup>2</sup>         | 11,912          | 12,218       | 30,111              | 30,883       | 43,712              | 44,833       | 55,976              | 57,411       |
| 6 mm <sup>2</sup>         | 17,476          | 17,925       | 42,201              | 43,283       | 69,172              | 70,946       | 79,590              | 81,631       |
| 10 mm <sup>2</sup>        | 30,343          | 31,121       | 66,847              | 68,561       | 98,701              | 101,232      | 128,462             | 131,756      |
| 16 mm <sup>2</sup>        | 44,719          | 45,866       | 102,013             | 104,629      | -                   | -            | -                   | -            |

**FLEXIBLE CABLES BS6500, IEC 60228 (300/500V)**

| Size                 |            |              | 300/500V CU/PVC/PVC |              | 300/500V CU/PVC/PVC |              | 300/500V CU/PVC/PVC |              |
|----------------------|------------|--------------|---------------------|--------------|---------------------|--------------|---------------------|--------------|
|                      | Registered | Unregistered | Registered          | Unregistered | Registered          | Unregistered | Registered          | Unregistered |
|                      | 2 - CORE   | 2 - CORE     | 3 - CORE            | 3 - CORE     | 4 - CORE            | 4 - CORE     |                     |              |
| 0.75 mm <sup>2</sup> | -          | -            | 10,053              | 10,311       | 12,730              | 13,056       | 15,695              | 16,097       |
| 1 mm <sup>2</sup>    | -          | -            | 12,555              | 12,877       | 16,450              | 16,872       | 21,158              | 21,701       |
| 1.5 mm <sup>2</sup>  | -          | -            | 15,113              | 15,501       | 21,042              | 21,582       | 27,088              | 27,783       |
| 2.5 mm <sup>2</sup>  | -          | -            | 23,832              | 24,443       | 32,784              | 33,625       | 42,084              | 43,163       |
| 4 mm <sup>2</sup>    | -          | -            | 36,156              | 37,083       | 49,001              | 50,258       | 67,080              | 68,800       |

- Note:**
- The above listed prices are of 90 meters coil
  - Prices are subject to change without prior notice
  - Cables not specified in above list and for ARMoured/NON-ARMoured POWER CABLES, please contact our sales department

**Head Office**

NEWAGE HOUSE, 33-K, Gulberg-II - Lahore | UAN : +92 42 111 777 300 | 042 35871701

Email : [info@newagecables.com](mailto:info@newagecables.com)

E - Store - [www.newagecables-estore.com](http://www.newagecables-estore.com)

**Factory / Works**

18-Km, Sheikhpura Road, Lahore. Ph: 042 - 371 - 68 941 - 42 - Web Page - [www.newagecables.com](http://www.newagecables.com)

For Flame Retardant , Low Smoke Zero Halogen and Power Cables up to 1000mm sq. prices to be provided on request.