

## Uninterruptible Power Supplies.

Product Name Alfa 600VA Line Interactive UPS

Model No 5306-H

Description Line Interactive UPS

Status New

Features

Line interactive design.

- Easy LED display.
- Provide AVR to stabilize input voltage.
- Provide lightning, surge, overload, and short-circuit protection.
- Built-in CCCV battery charger and battery over drain protection.
- Auto restart when AC recovery.
- Cold start function. (DC power on)
- Tel / Modem / Fax / Internet surge suppression.
- Compact design fits your working environment.

MODEL	Alfa	5305	5306
Capacity	VA / Watts	500VA/300W	600VA/360W
	Voltage	115Vac / 230Vac	
Input	Voltage Range	86Vac~136Vac / 172Vac~272Vac	
	Frequency	47Hz~53Hz / 57Hz~63Hz	
Output	Voltage (Batt. Mode)	115Vac / 230Vac ±10%	
	Frequency	50Hz or 60Hz ±1Hz	
	Waveform	Simulated Sine-wave	
	Transfer time	< 6ms (typical)	
	Outlets: IEC-320 / NEMA 5-15R	2 / 2	
Battery	Battery Type	12V/7AH*1pcs	12V/7AH*1pcs
	Recharge time	5 hours to 90% after complete discharger	
	User`s Replacement	No	
	Battery Protection	Over discharger protection, short circuit protection by fuse	
	Advance Battery Management	Yes	
	Battery Back-up Time	10mins (Load with 1PC) 20mins (Load with 1PC)	
Function	Display	LED status indicator for Line-on, Back-up, UPS cut-off	

	Alarm	Buzzer on for Back-up mode, Battery low	
	Output Short protection	AC fuse & electronic circuit (Line mode); electronic circuit (back-up mode)	
	Modem / Phone Protection	RJ-11	
	Lightning / Surge Protection	320 Joules	
	AVR ( Auto. Voltage Regulation)	Yes	
	DC-start Function	Yes	
	Auto. Restart UPS	Yes	
	Over / Under Voltage Protection	Yes	
Environment	Safety Standard	CE ( EN50091-1, EN62040-1-1)	
	EMC Standard	FCC Part 15 Class B, CE (EN50091-2, EN55011, EN61000-3-2, EN61000-3-3)	
	Operating Temperature	0°C ~ 40°C	
	Relative Humidity	0-90%, non-condensing	
	Audible Noise	< 40dBA at 1 meter	
Physical	Dimension, D*W*H	265*90*176 mm	
	Net Weight	6.5 kgs	6.p kgs
Design, Manufacture, Services	ISO 9001		



Rs 7,000

## Product Detail

Category Name      UPS

Product Name      Alfa Digital 1000VA UPS

Model No      8310-H

Description      1000 VA Line Interactive UPS

Features

- User-friendly LED display. □ Provide boost and buck AVR to stabilize input voltage.
- Provide lightning, surge overload, and short-circuit protection. □ Built-in CCCV battery charger and battery over drain protection.
- No load auto shutdown (Dip switch setup). □ Auto restart when AC recovery.
- Buzzer alarm auto-reset (Dip switch setup).
- Cold start function (DC power on). □ Tel / Modem / Fax / Internet surge suppression.
- Optional Bundle software: Automatically save your valuable files before auto shutdown.

MODEL	ALFA DIGITAL		8310AL	
Capacity	VA / Watts	1000VA/600W		
Input	Voltage	115Vac / 230Vac		
	Voltage Range	86Vac~144Vac / 172Vac~288Vac		
	Frequency	47Hz~53Hz / 57Hz~63Hz		
Output	Voltage	115Vac / 230Vac ±10%		
	Frequency	50Hz / 60Hz ±1Hz		
	Waveform	Simulated sine-wave		
	Transfer Time	<6ms (typical)		
	Outlets: IEC-320 / NEMA 5-15R	4 / 4		
Battery	Battery Type	12V/4.5AH*2Pcs 7AH*2Pcs		
	Recharge time	5 hours to 90% after complete discharger		
	User`s Replacement	No		
	Battery Protection	Over discharger protection, short circuit protection by fuse		
	Advance Battery Management	Yes		
	Battery Back-up Time	30mins (Load with 1PC)	40mins (Load with 1PC)	
Function	Display	LED indicator for line-on, battery back-up, AVR protection, load and battery level, overload and UPS cut-off		
	Alarm	Buzzer on for back-up mode, Battery low, Over load		



Rs 12,375

Category Name	UPS
Product Name	Alfa 3KVA Line Interactive
Model No	Alfa 3330-H
Description	3KVA Line Interactive UPS

## Features

### Line interactive design.

- User-friendly LED display.
- Provide boost and buck AVR to stabilize input voltage.
- Provide lightning, surge, overload, and short-circuit protection.
- Built-in CCCV battery charger and battery over drain protection.
- No load auto shutdown (Dip switch setup).
- Cold start function (DC power on).
- Buzzer alarm auto-reset (Dip switch setup).
- Tel / Modem / Fax / internet surge suppression.
- Auto restart when AC recovery.
- Optional Bundles software: Automatically save your valuable files before auto shutdown.
- Microprocessor design for true RS-232 (Option).

## Alfa-3330 SPECIFICATION

MODEL	Alfa		3330-H		
Capacity	VA / Watts		3000VA/1800W		
Input	Voltage	115Vac / 230Vac			
	Voltage Range	86Vac~144Vac / 172Vac~288Vac			
	Frequency	47Hz~53Hz / 57Hz~63Hz			
Output	Voltage	115Vac / 230Vac ±10%			
	Frequency	50Hz / 60Hz ±1Hz			
	Waveform	Simulated sine-wave			
	Transfer Time	< 6ms (typical)			
	Outlets: IEC-320 / NEMA 5-15R	6 / 4			
Battery	Battery Type		9AH*4 Pcs		
	Recharge time	5 hours to 90% after complete discharger			
	User`s Replacement	Yes			
	Recharge Protection	Over discharger protection, short circuit protection by fuse			
	Advance Battery Management	Yes			
	Battery Back-up Time	It depends on connecting loads			
Function	Display	LCD indicator for line on, battery back-up, AVR protection, load and battery level, overload and UPS cut-off			
	Alarm	Buzzer on for back-up mode, Battery low, Over load			
	Output Short Protection	AC fuse and electronic circuit (Line mode); electronic circuit (back-up mode)			
	Communication Port (DB9)	RUPS-2000 software for windows 95/98/NT/2000/ME/XP			
	Modem /				



Rs 32,375

#### APC UPS Rates

650 VA	Rs 12,000
1 KVA	Rs 39,000
1.5 KVA	Rs 65,000
2.2 KVA	Rs 100,000
3 KVA	Rs 150,000