



Tawanai Energy

30 HP submersible pumps and motors

Date : 17 May 2018

Combination 1

Pump 6-SS-3-23 Rs. 123,500

30 HP 4-30-HP-SM : Rs 107,900

Combination 2

Pump 6-SS-4-14 Rs 91,000

35 HP 4-35-HP-SM : Rs. 130,000

92 331 2036 422

tawanai@atrc.net.pk

<http://atrc.net.pk/tawanai>

PERFORMANCE DATA 50Hz

MODEL		Power		DELIVERY								N=2850 1/min	
1-220V/240V	3-380V/415V	KW	HP	Q	m ³ /h	0	6	12	18	24	30	36	42
					1/min	0	100	200	300	400	500	600	700
6-SS-M3-2	6-SS-3-2	2.2	3	H(m)	23	23	22	20	19	16	13	8	
6-SS-M3-3	6-SS-3-3	3	4		35	34	32	30	28	24	19	12	
6-SS-M3-4	6-SS-3-4	4	5.5		47	46	43	40	38	33	25	17	
6-SS-M3-5	6-SS-3-5	5.5	7.5		59	57	54	50	47	41	32	21	
	6-SS-3-6	5.5	7.5		70	69	65	60	56	49	38	25	
	6-SS-3-7	7.5	10		82	80	75	70	66	57	45	29	
	6-SS-3-8	7.5	10		94	91	86	81	75	65	51	33	
	6-SS-3-9	9.2	12.5		105	103	97	91	85	73	57	37	
	6-SS-3-10	9.2	12.5		117	114	108	101	94	82	64	41	
	6-SS-3-12	11	15		140	137	129	121	113	98	76	50	
	6-SS-3-14	13	17.5		164	160	151	141	132	114	89	58	
	6-SS-3-16	15	20		187	183	172	161	150	131	102	66	
	6-SS-3-18	18.5	25		211	206	194	181	169	147	115	74	
	6-SS-3-20	18.5	25		234	229	215	201	188	163	127	83	
	6-SS-3-22	22	30		257	252	237	221	207	180	140	91	
	6-SS-3-24	22	30		281	274	258	242	226	196	153	99	
	6-SS-3-26	22	30		304	297	280	262	244	212	166	107	
	6-SS-3-28	26	35		328	320	301	282	263	229	178	116	
	6-SS-3-30	26	35		351	343	323	302	282	245	191	124	

MODEL	Power		DELIVERY									n≈2850 1/min	
	KW	HP	Q	m ³ /h	0	30	36	42	48	54	60	66	
l/min				0	500	600	700	800	900	1000	1100		
3 ~ 380V -													
6-SS-4-2	3	4	H (m)		27	22	20	18	16	14	10	6	
6-SS-4-3A	4	5.5			37	29	27	24	21	16	12	8	
6-SS-4-3	5.5	7.5			41	33	30	28	25	21	15	9	
6-SS-4-4	7.5	10			54	43	40	37	33	27	20	12	
6-SS-4-5	7.5	10			68	54	50	46	41	34	25	15	
6-SS-4-6	9.2	12.5			82	65	60	55	49	41	31	19	
6-SS-4-7	11	15			95	76	70	64	58	48	36	22	
6-SS-4-8	13	17.5			109	87	80	74	66	55	41	25	
6-SS-4-9	15	20			122	98	90	83	74	62	46	28	
6-SS-4-10	15	20			136	108	100	92	82	68	51	31	
6-SS-4-11	18.5	25			150	119	110	101	91	75	56	34	
6-SS-4-12	18.5	25			163	130	120	110	99	82	61	37	
6-SS-4-13	22	30			177	141	130	120	107	89	66	40	
6-SS-4-14	22	30			190	152	140	129	115	96	71	43	
6-SS-4-16	26	35			218	174	160	147	132	110	82	50	
6-SS-4-18	30	40			245	195	180	166	149	123	92	56	